




F **FLOATING**
 design floating floor



Embossed Wearlayer
 with PU finishing
 Design film
 Comfort layer
 High-density fiberboard
 Comfort & Acoustic Cork Backing



**Floating floor
 with a strong
 Click System**



CLASS **33** / **42**



COLLECTIONS	LUNGO	LUNGO SENSES	EXTENDED SENSES	METROPOLITAN	SCANDINAVIAN
Dimensions EN 427 / Thickness EN 428	1800 x 220 x 10,8 mm	1800 x 220 x 10,8 mm	1500 x 220 x 10,8 mm	1200 x 210 x 9,3 mm	1200 x 210 x 9,3 mm
Impact Sound Reduction en 140	18 dB	18 dB	18 dB	17 dB	17 dB
Emboss / Surface	Regular Wood Semi-matte	Registered Wood Semi-matte	Regular Wood Semi-matte	Regular Wood Semi-matte	Regular Wood Semi-matte
Classification EN 16511	33	33	33	33	33
Weight EN 430	11 kg/m ²	11 kg/m ²	10 kg/m ²	10 kg/m ²	10 kg/m ²
Fire Performance EN 13501			Bfl - s1		
Anti-sliding properties EN 13893			Class DS		
Formaldehyde emission EN 717-1			Class E1		
Content of PCP CEN / TR 14823			Not to declare		
Dimensional Stability after exposure to heat EN ISO 23999:2012			-0.1%		
Abrasion Resistance EN 15468, Annex A			2500		
Static Indentation EN ISO 24343			0,04 mm		
Resistance against impact (big ball) EN 13329			No visible change		
Chemical Resistance EN 433			Class 0		
Determination of the effect of a castor chair EN 425			No visible change		
Determination of the effect of a furniture eg EN 424			No visible change		
Microscratch resistance EN 16094			MSR-A2 / MSR-B1		
Resistance against staining according to EN 438-2:2016	Coffee: grade 5 / NaOH: grade 4 / H2O2: grade 5 / Shoe polish: grade 5 / Shoe polish: grade 5				
Locking strenght ISO 24334:2006					
- short side joints			5.8 kN/m		
- long side joints			6.9 kN/m		
Underfloor Heating			Approved 27°C		
Thermal Resistance EN 12524			0,088 m ² /W		
Emissions Value			In conformity with AgBB		
Resistance to Fading ISO 105 B02			6/8 Good		

